## PRODUCT SPECIFICATION





## XIDDR

LIBERATE YOUR MOBILE RADIO

## **Secure Wireless Microphone**

The incredibly compact, lightweight and patented X10DR® secure wireless microphone extends the power of the mobile radio into the palm of your hand, both in and out of the vehicle.

Based on the highly robust IEEE 802.15.1 standard, the 2nd generation X10DR continues to revolutionize mobile network design by increasing user functionality and mobility whilst reducing infrastructure investment. This visionary solution provides users out of vehicle communications with the power and performance of the mobile radio.

The X10DR cuts the cord and for the first time puts the microphone and radio system access into the users hand when away from the vehicle, delivering true mobility without system compromise.

The X10DR unleashes the power of your mobile radio allowing wireless communication with a fixed mounted or vehicle mobile radio up to 500 meters and more.\* Now users can communicate with enhanced clear audio, with the power and range of a mobile radio whilst not being tied to the vehicle, allowing the user to be truly mobile in every operational environment.



SECURE WIRELESS COMMUNICATION via your vehicle's mobile radio



## **Specifications**

Subject to change or improvement without notice

The equipment has been designed to meet the following global specifications:

2.40-2.48GHz Frequency Hopping Spread Spectrum Frequency:

802.15.1 based derivative Protocol:

RF Power: Handset <100mW / Gateway <100mW

RF Sensitivity: >90dBm

**Battery Type:** 3.7V @1450mA Lithium Polymer **Battery Life:** >15 Hours @ 30% receive time **Encryption:** Elite: Full AES128 / Pro: Basic AES

RF Connectors: **RP SMA Female** >300mW @5% THD Rated Audio/Dist:

Hirose Audio port: Standard 3.5mm Audio port: Standard Operating Voltage: 7-16VDC

**Operating Temp:** -20°C to +55°C /-4°F to +122°F

**Dimensions:** 88 x 28 x 63mm (handset) 80 x 80 x 60 (gateway)

Weight: 150 grams (handset) 125 grams (gateway)

**Shock & Vibration:** Mil Std 810 C/D/E/F

Humidity/Rain/Dust: IEC529, IP55 Pro handset / IP67 Elite handset

Type Acceptance: CE, FCC, IC, Aust/NZ, Other as advised.

> FCC ID: 2AGEY-XH2 / 2AGEY-XG2 IC:11443A-XH2/ IC:11443A-XG2

**( f (1)** 0682









